

# AI FACE RECOGNITION Device guide

[www.aidgroup.com.co](http://www.aidgroup.com.co)



## Table of contents

### Brand introduction

Product R & D background .....	1
--------------------------------	---

### Product hardware

Product hardware .....	2
Product promotion .....	3-6
Product design .....	7
Product specification and dimension .....	7
Product hardware introduction .....	7
Product parameters .....	8-9
Installation diagram .....	10
Product package design .....	11
Renderings .....	12
Supporting equipment for AI recognition system .....	13
Installation Instructions .....	14
Gate machine .....	14
Tester Requirements Diagram .....	15
Installation .....	16
Backstage management .....	17
APP management .....	18

## Table of contents

Scenario solution cases	19-20
Recommended solutions for public transportation	21
Parameters and specification for environment application	22
Recommended solutions for schools and government	23
Parameters and specification for environment application	24
Recommended solutions for corporate offices	25
Parameters and specification for environment application	26
Recommended solutions for hotels and shopping malls	27
Recommended solutions for construction sites, stations, and makeshift sites	28
Parameters and specification for environment application	29
Recommended solutions for residential communities	30
Parameters and specification for environment application	31
Recommended solutions for makeshift checkpoints, stations, etc.	32
Parameters and specification for environment application	33



### The novel coronavirus has arrived:

During the Spring Festival of 2020, the novel coronavirus quickly spread to the whole country. The epidemic of coronavirus has interrupted the traditional Chinese New Year holiday and also had a huge impact on the economic operation of China. At the same time, with the rapid spread of the epidemic worldwide, the prevention and control of the epidemic has become the world's top priority. The epidemic being under control, the resumption of production is under way:

Guangdong is a Province with the largest economic scale and the largest population in China.

According to statistics, the permanent population in 2019 increased by 1.75 million to 115.21 million, including migrant workers and immigrants. There is a large number of people migrating on a daily basis. With the gradual abatement of the epidemic within China, the resumption of production in our province has been carried out in an orderly manner. Schools at all levels, enterprises, and other important places have ushered in the peak of population migration, which poses great challenges for epidemic prevention and control in various industries.



### 1x Thermal imaging sensor

When the equipment is running, it detects the temperature difference and analyzes it. It will automatically warn when the detected temperature exceeds the set value.

### 2 x 2MP AI HD camera

The camera is analyzed by a database algorithm, Fast face recognition comparison, and judgment.

### 24 x LED white light

LED fill light can help camera system to shoot, Can fill the scene according to the actual situation.

### 2 x LED Infrared Light

Better capture of images at night to achieve more uniform light on the screen.

### 1.2 mm thick tempered glass


High-definition clear picture quality, no dropped frames,color balance.

### 7 inch IPS HD screen

Clear picture quality in HD No dropped frame color balance.

### All aluminum body

Integrated aluminum alloy forming process to achieve uniform heat dissipation.



# AI Ultra-precision Human Body Temperature Measurement Face Recognition Device

Assist in scientific epidemic prevention (FK02GYW)



Forehead temperature  
measurement



Mask recognition



Identification



Fever warning



Data query



# Functions and Features



## Accurate Temperature Measurement

Error of plus or minus 0.3 °C



## Two-eye recognition

Support two-eye live human face detection



## Mask Detection

No need to remove the mask, automatically capture the face for identification



## Fast recognition

200ms face recognition



## 30,000-Person Face

Support 30,000 local face storage



## High Recognition Rate

Face recognition accuracy rate is as high as 99.5%



## Fill-in light

Built-in fill-in light, low-light situations applicable



## Embedded Systems

Low power consumption, high stability



## Backstage Management

Abnormal records, equipment management, personnel management



## Mobile APP

Visitor management, information push

## Ensure safety during resumption of production

## Combat the epidemic effectively

Temperature error range  $\pm 0.3$  °C

Detect body temperature accurately, intelligent warning in case of fever

Normal body temperature


**36.0°C-37.3°C**

Hypothermia

**37.3°C-38.5°C**

High body temperature

**More than 38.5°C**



# SECURITY

Eliminate the hidden danger of infection through traditional means of laissez-passer



Traditional traffic

**Fingerprint identification, swiping the ID card**

Direct contact, which poses a serious hidden danger of cross infection

**X**

**Vs**



Face traffic


**AI face recognition**  
0.5-1.3m can open the door

On-contact, safe and reliable

**✓**

# EFFICIENT

Improve temperature measurement and disease prevention and control efficiency




Manual temperature measurement

**Manual temperature measurement**

Close distance when measuring temperature

**X**

**Vs**



Intelligent temperature measurement


**Laissez-passer through face recognition**  
**Complete temperature measurement at the same time**

No need for second manual intervention

**✓**

# INTELLIGENT


AI intelligent disease prevention and control , intelligent data analysis




Manual prevention and control

**Manual disease prevention and control, manual data analysis**

Labor-intensive and time-consuming, with possibilities of errors and missing out data.




VS





Smart temperature measurement

**Face recognition+temperature measurement dual identification**

Quickly record entrance and exit information and temperature measurement information.



## APPLICATION SCENARIOS






**Product design**



**Product specification and dimension**




**Size:220×112×24**

## Product specification and parameters

System	
Main Processor	MX3520
Operating System	Embedded LINUX
RAM	DDR3 512MB
ROM	EMMC 8GB
Screen	
Dimensions	7 inch IPS HD LCD screen
Resolution	736*1280
Camera	
Type	2MP night vision living detection camera
Sensor	1/5" GC2145
Resolution	NIR 800*600 15fps
Lens	2.4mm
Camera	
Type	Daily camera
Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor IMX307
Resolution	Color 1920*1080 30fps
Lens	4.5mm
Body temperature detection	
Measuring site	Forehead
Temperature range	36-42 °C
Temperature measuring distance	0.5-1.3m, 0.75m is the best
Temperature measurement accuracy	± 0.3°C
Temperature measurement response	Face library people: 1.5-2s, Strangers: 2.5-3s
Face recognition	
Detection Type	Support living detection, Mask detection
Face recognition distance	0.5-1.5m
Face database capacity	Max support 30,000 faces
Face Angle	(Daytime) vertical viewing 58°-60°, horizontal viewing 35°; (Living body) vertical viewing 48°-50°, horizontal viewing 36°
Occlusion	Ordinary glasses and short sea retention have no effect on recognition.
Expression	Under normal circumstances, slight expressions do not affect recognition.

Response Speed	About 200ms
Face exposure	Support
Local Storage	Support storage of 25,000 records
Recognition area	Full image recognition
Upload Method	TCP, HTTP, MQTT
Network Functions	
Network protocol	IPv4, TCP/IP, HTTP
Security Mode	Authorized username and password
Event linkage	Voice broadcast, Abnormal event upload to the platform
System Upgrade	Support remote upgrade
Accessories	
Supplementary light	IR light, LED white light
Audio out	Built in Speaker support voice broadcast after successful recognition
Interface	
Network Interface	RJ45 10M/100M Network Adaptation
Alarm Output	1 Channel relay output(NC or NO)
RS485 interface	Support
Wiegand interface	Support Wiegand 26, 34, 66 protocols
Reset key	Support
General	
Housing	Metal body and bracket, Plastic screen, IP66
Operating Temperature	-20 ° C ~ 60 ° C
Working humidity	10% -90% Non-condensing
Storage Temperature	-40 ° C ~ 70 ° C
Storage humidity	5% -95% Non-condensing
Power Supply	DC12V
Power dissipation (maximum)	= 12 W
Dimensions (mm)	219 (W) * 111 (H) * 21.5 (T)
Bracket size (mm)	Φ 27*189 Extension rod Φ 27*390
Installation Method	Desktop Installation/Floor Installation







Entrance →

← Exit



Gate machine




Regular pole




Wall-mount




Lengthening pole



Desktop



Vertical-mount (children)




Vertical-mount (adults)






Supporting equipment for AI recognition system




Gate Machine access control solution



Gate Machine access control solution


## Installation Instructions

### Bracket Type



Choose the correct type of bracket according to the actual situation, insert the mounting bracket of the face temperature measuring machine into the fixing hole of pole, fix the device nut, adjust the face thermometer to an appropriate angle ( vertical included angle  $5^{\circ}$ - $15^{\circ}$  ).

### Gate machine



Make a hole with a diameter of 35mm on the gate machine, the recommended position is 1/3 to 1/4 of the entrance end. Insert bracket of face recognition temperature device into the hole, fix the device nut from the inside of the gate, adjust face thermometer to an appropriate angle ( vertical included angle  $5^{\circ}$ - $15^{\circ}$  ).

## Tester Requirements Diagram

When import photo, please make sure photo with frontal faces, do not wear hat, sunglasses, or wear heavy makeup. When test temperature, make faces in circle of the device. Do not block your forehead. If you have bangs, you can lift them up.

Frontal Face ✓



Side head ✗



Side face ✗




Head up ✗



Head down ✗



Face entry/ head position instructions



As shown in the pictures

Installation Notes

Avoid backlighting, direct sunlight, direct sunlight through windows, slant sunlight through windows, and light at short range.

Installation environment parameters



Candle: 10Lux





Light bulb: 100~850 Lux




Daylight: greater than 1200 Lux

When the device is installed indoors, keep it more than 2 meters away from the light source, and more than 3 meters away from doors and windows. Avoid direct sunlight or light at short distance.



Avoid backlighting, direct sunlight, direct sunlight through windows, oblique sunlight through windows, and light at short distance.



X Backlighting


X Direct sunlight

X Direct sunlight through windows

X Slant sunlight through windows

X Light at short range

## Backstage management



### Device management

Cross network segment search, batch operations, online upgrades, group management.

### Personnel management

Group management, batch import photos, Multi-form authorization.

### Visitor management

Multi-end appointment, traceable access records.

### Report management


Trajectory tracking, record tracing, temperature monitoring, mask wearing records, abnormal notification.

### Data center


Personnel flow statistics, daily visitor statistics, abnormal temperature monitoring, abnormal trend distribution statistics, fever statistics.



## App management



Message push



Visitor appointment

←

Visit information

Visitor information

Photo

Name

Annie

Gender

Female

Phone

136506650586

Visit message

Visit reason

Participate in a speech contestant

35/200

Authorize message

Start time

2020-04-29 11:01:00

End time

2020-04-30 11:01:00

Visitor details


## Real scenario solution case

Application scenarios: Government, hospitals, schools, office buildings, factories, supermarkets, hotels, airports, railway stations, tourist attractions, etc.


Covered countries: France, Italy, Germany, South Korea, Qatar, Thailand, Japan, United Kingdom, Russia, Turkey, etc.

Installation scenarios: Crowded entrance, temporary control area, indoors.

Ambient temperature of equipment: 10 °C-50 °C



Real scenario solution case



## Recommended solutions for public transportation

### Contactless induction

Fast face recognition

### Fast pass

200ms fast recognition

### Intelligent fever warning


When the temperature exceeds the set value, the device will make a voice broadcast and this record will be saved in the database as abnormal.

### No mask warning


When a person does not wear a mask, the device will make a voice broadcast and this record will be saved in the database as abnormal.



## Parameters and specification for environment application



**Intensive public transportation scene**







## Recommended solutions for schools and government


The AI face recognition terminal is suitable for various real-name verification scenarios of humanoid entrances, such as schools, governments, office buildings and other pedestrian entrances.

By installing the AI face recognition terminals in the crowded areas like teaching buildings, government entrances, and office buildings, we can measure temperature of passers-by in real time, and strengthen the prevention and control management and health monitoring, effectively coping to the peak of resumption of schooling and work, and minimize the risk to achieve a safety campus.






Temperature Measuring point in School



Temperature measurement channel



Government temperature measurement and the security checkpoint

## Recommended solutions for corporate offices

### Contactless induction

Fast face recognition

### Fast pass


200ms fast recognition

### Intelligent fever warning

When the temperature exceeds the set value, the device will make a voice broadcast and this record will be saved in the database as abnormal.

### No mask warning


When a person does not wear a mask, the device will make a voice broadcast and this record will be saved in the database as abnormal.






## Parameters and specification for environment application

Application scenarios: office, dense area of up & down stairs, companies and factories.



**Temperature Measuring area in office elevator**




**Temperature Measuring area in reception**

## Recommended solutions for hotels and shopping malls

### Integrated channel for temperature measurement and disinfection

The integrated temperature measurement and disinfection channel has functions of body temperature measurement and disinfection. The overall structure is shown in the pictures below, and the size can be customized according to requirements. Function modules include: main-body tempered glass channel frame, AI temperature measurement recognition terminal, control box, atomization system. Ambient temperature: 10 °C-50 °C  
The device is practical, efficient and easy to install.



Glass Passage



Facial recognition terminal starting



Facial recognition terminal installation




Final result

## Recommended solutions for construction sites, stations, and makeshift sites




The movable makeshift house is also called "combined box house" or "container-like house". It uses color steel plate as the skeleton, laminboard as the enclosure material, and standard modular series for space combination. The components are connected by bolts. It is a new concept of environmentally friendly and economical movable makeshift house, it can be used as exhibition halls for real estate development companies, product sales exhibition halls, temporary reception centers, commercial temporary offices, shops, etc.



## Movable makeshift house



## Movable makeshift house




## Recommended solutions for residential communities

The rain shed, which is made of polycarbonate solid sheets, has characteristics of good light transmission, impact resistance, flame etardancy, low temperature resistance, sound insulation, etc. The most prominent features of the rain shed are with high strength, excellent durability, fire resistance and flame retardancy, good cleanability and freedom from the effect of ultraviolet radiation. It also has a service life of about 15 years. It is suitable for campuses and stadiums. It can withstand the sunlight for a long time without being yellow or fogging, with stable quality, no deterioration, light weight, easy to disassemble and easy to transport, and no potential risk of crushing heavy objects.




Parameters and specification for environment application

Application scenarios: residential communities, intensive public residences, student apartments, factory dormitories.



Makeshift color-steel sheet rain shed installation



## Recommended solutions for makeshift checkpoints, stations, etc.

The tent is suitable for temporary site such as checkpoints and stations.

### Features

Low cost, simple and flexible assembly and disassembly, fast transportation, convenient storage and space saving.

### Common types of tents



Simple skeleton tent



Steel structure rain shed




Military rain shed




Medical thermal insulation tent

## Outdoor temporary passageway



Semi-enclosed temperature measurement site



Fully open temperature measurement place



